A-SERIES CLIMBING/ POSITIONING HARNESS

806000 / 806100
806400 / 806500
806600



INSPECTABLE

- Tattletale™ webbing has an interior ply of contrasting bright red "strength" yarns that increase webbing strength to 7000 lbs (31kN) and instantly reveal cuts or abrasion
- Built-in impact load indicators
- Bar-coded individual serial numbers for traceability
- Indelible serial number in back plaque

COMFORTABLE

- "Floating" thigh stitching reduces binding
- Improved geometry brings buckles to front of thigh
- Angled stitching for "tailored" sub-pelvic fit
- Extra large back pad eliminates dangerous 'D-ring droop'

DURABLE

- No elastic webbing
- Heat-set labels won't come off
- Corrosion resistant grommets
- Extra thick woven (not sewn) seat webbing for added durability

TATTLETALE™ WEBBING

TattleTale™ web is inspectable web. All load-bearing straps in Fall Safe harnesses and lanyards have a red inner core (or a yellow core in black webbing) which becomes exposed when the web becomes damaged by cuts or abrasion. Red that shows through is not a "red light" signaling the user to stop using the equipment, it simply "tells" the user that the equipment needs closer inspection, and where to look. The webbing helps again by giving the Competent Person (the expert) the information needed to judge how deep the cuts or abrasions are, so the seriousness of the issue can be determined. Call Fall Safe at 800.362.2826 for complete inspection procedures.

* Please Note: Harness sizing as follows:
  8XX1XX = Small
  8XX4XX = X-Large
  8XX5XX = XX-Large
  8XX6XX = Big Boy