IRONMAN™ CONSTRUCTION POSITIONING HARNESS

812000 / 812000C
812100 / 812400
812410 / 812500
812515 / 812600



PRODUCT FEATURES & SPECIFICATIONS

- Tattletale™ webbing has an interior ply of contrasting bright red "strength" yarns that increase webbing strength to 7000 lbs (31kN) and instantly reveal cuts or abrasion
- Built-in impact load indicators
- Bar-coded individual serial numbers for traceability
- Indelible serial number in back plaque
- Removable back support/tool belt, shoulder padding
- Fall Safe Quick-Adjust™ torso adjustment buckles
- Slotted positive engaging chest buckle
- "Floating" thigh stitching reduces binding
- Improved geometry brings buckles to front of thigh
- Angled stitching for "tailored" sub-pelvic fit
- Extra large back pad eliminates dangerous 'D-ring droop'
- No elastic webbing
- Heat-set labels won't come off
- Extra Heavy-Duty Corrosion resistant leg grommets
- Extra thick woven (not sewn) seat webbing for added durability

WHAT IS TATTLETALE™ WEBBING?

TattleTale™ web is inspectable web. All load-bearing straps in Fall Safe harnesses and lanyards have a red inner core (or a yellow core in black webbing) which becomes exposed when the web becomes damaged by cuts or abrasion. Red that shows through is not a "red light" signaling the user to stop using the equipment, it simply "tells" the user that the equipment needs closer inspection, and where to look. The webbing helps again by giving the Competent Person (the expert) the information needed to judge how deep the cuts or abrasions are, so the seriousness of the issue can be determined. Call Fall Safe at 888.362.2826 for complete inspection procedures.

* Please Note: Harness sizing as follows:

8XX1XX = Small
8XX4XX = X-Large
8XX5XX = XX-Large
8XX6XX = Big Boy