



TECHNICAL DATA SHEET

SELF-RETRACTING DEVICE LE (SRD-LE)

PeakWorks offers a new series of self-retracting devices that are third-party certified to the newest ANSI Z359.14-2021 standard. The Tie-Back SRD Class 2 leading-edge device serves as an all-in-one self-retracting lifeline and anchorage connector, thus reducing the amount of equipment required on the job site. The device is approved for both vertical and horizontal applications with a setback distance of 12 inches.

WARNINGS: See the Operating and Maintenance Instruction Manual for details.

FEATURES:

- Approved for use in vertical and horizontal applications
- Tested and approved for foot level tie-off
- No shock pack required
- Maximum Arrest Distance: 42 in (1.07 m)
- Average Arrest Distance: 27 in (0.69 m)
- Maximum Arrest Force: 1,800 lbs (8 kN)
- Average Arrest Force: 678 lbF (3.02 kN)
- Minimum setback distance from edge: 12 in (30 cm)
- Third-party certified to ANSI Z359.14 Class 2
- All LE products are clearly marked to ensure the correct SRD is used for Leading Edge applications



ORDERING INFORMATION

PRODUCT #	NEW MODEL #	DESCRIPTION	LENGTH OF SRL
V845528109TBLE	SRD-54T54-9TBLE	SRD – Twin Leg with Tie-Back – 9'	9 FT

STANDARD COMPLIANCE

Standard Certified to ANSI Z359.14-2021

TECHNICAL SPECIFICATIONS

HOUSING STYLE	LIFELINE SPECIFICATIONS		BODY FALL ARREST D-RING CONNECTION	ANCHOR POINT STYLE	
Aluminum	Dyneema® Webbing 1 in wide x 0.07 in thick (25 mm wide x 1.75 mm thick)		5,000 lb Gate Snap Hook	Swivel Mount Harness Attachment	
SINGLE LEG/ TWIN LEG	FALL ARREST	RESCUE/ RECOVERY	ANCHOR MOUNTING POSITION	LE (Y/N)	EXTERNAL SHOCK PACK (FOR LE)
Twin	Yes	No	Anchorage Connector	Yes	No

WEIGHT CAPACITY: 110–310 lbs (50–141 kg) capacity for 1 worker (combined weight of person, tools, clothing, etc.)

STORAGE: Store in a cool dry place away from chemicals, water, corrosive environments, and source of heat or spark

OPERATING TEMPERATURES: -40° F to 122° F (-40° C to 50° C)



surewerx.com

325 Corporate Drive
Elgin, IL 60123
USA

Toll Free Tel: 1-800-323-7402
Fax: 847-717-8419
email: orders.usa@surewerx.com