HORIZONTAL LIFELINE STANCHION

6151-1
6178-1
6163-1



SPECIFICATIONS

- Single-Point Anchor Capacity: 1 User*
- Multi-Span HLL Capacity: 1-4 Users (See instructions and HLL Wizard for further details)*
- *Max. user capacity is 310 lbs per user, including clothing, tools and equipment.

For other anchorage/base options, please contact Fall Safe for assistance.

Stanchions are elements of an engineered fall arrest system and are not stand-alone products. For complete system details, please consult with the instructional materials or contact Fall Safe for assistance.

Meets the requirements of OSHA 1910.66 and 1926.502. Anchorage elements meet the requirements of ANSI Z359.1-2007.

COMPATIBLE WITH THE FOLLOWING ITEMS:

- 6169 Stanchion Receiver for L Rebar
- 6170 Looped Rebar Receiver Bracket
- 6230 HLL Stanchion Beam Clamp
- 6231 HLL Stanchion Beam Clamp
- 6235 HLL Stanchion Beam Clamp
- 6240 HLL Stanchion Beam Clamp
- 6260 Nelson Stud Bracket Base
- 6173 Concrete Beam Reciever
- 6181 Concrete Embed Sleeve
- 6185-10 Stanchion Receiver
- 6262 Modular Rebar/Shear Stud HLL Bracket
- 6263 Modular Rebar/Shear Stud HLL Bracket Narrow

Standard sizes:
6151 - 60" (1.5 m)
6178 - 72" (1.8 m)
6163 - 84" (2.1 m)