# MICRO-LOC® HOT WORK SRL-P WITH REBAR HOOK, TWIN

**4266106-1**




Introducing the new Fall Safe Micro-Loc® Hot Work Personal Self-Retracting Lanyard.

The Micro-Loc Hot Work was designed to offer you versatility in most construction situations. When you have hot work being performed, You not only have to protect the person doing the work but, also everyone around them.

Fall Safe is proud to offer a solution that is affordable enough to ensure that all your workers are protected in these situations.

It exceeds OSHA requirements in Subparts I and M as well as all ANSI/ASSP Z359.14 Class 1 requirements, with shorter activation and arrest distances. The Micro-Loc® Hot Work will keep workers safe without overburdening them or your bottom line.

## MICRO-LOC SPECIFICATIONS:

- Lifeline Web: 1" 6,000 lb. Kevlar®
- Frame: High-Strength Alloy Steel
- Swivel: High-Strength Alloy Steel
- Main Spring: Texture Rolled Carbon Steel
- Housing: Nylon 6/6 Thermoplastic
- Pawls: Hardened Stainless Steel
- Sperrad: High-Strength Alloy Steel
- Housing Dimensions: 3.5" x 2.5" x 3.4"

## PERFORMANCE SPECIFICATIONS:

- Overhead Arrest Distance: 24" or less
- Below D-Ring Arrest Distance: 42" or less
- Average Arrest Force: 900 lbs or less
- Max. Arrest Force: 1,800 lbs or less

## MAXIMUM WORKING CAPACITY:

400 lbs (Including tools and equipment)