

SHOCK ABSORBING LANYARD - SP - SINGLE LEG - SNAP HOOKS - 4' (1.2 M) - 110 – 220 LB CAPACITY



Product # **V8104604** | Model # **SA-5400-4**

SP (Shock Pack) lanyards are comprised of tear webbing which is woven in a manner that allows the webbing to tear when it has a load applied to it. This tearing absorbs a significant amount of downward force under load, reducing injury. This tear webbing is folded and shrink-wrapped into a compact 1 x 2 x 6 (2.5 x 5 x 15 cm) pack that is sewn into the lanyard next to the body connector.

- Certified to CSA Z259.11-05 standards
- Made with a superior grade, heavy-duty 1" (25 mm) polyester webbing for maximum strength with tear webbing shock absorber
- PeakWorks E4 SP lanyards have a capacity range of 110–220 lbs (50–100 kg)



TECHNICAL SPECIFICATIONS

| | |
|--------------------------------|-----------------------------|
| Anchor Hook Type | Snap Hook |
| Body Hook Type | Snap Hook |
| Deceleration Distance | 4 ft at 220 lbs |
| Leg Type | Single |
| Length (ft.) | 4 |
| Length (m.) | 1.2 |
| Material | Polyester Webbing |
| Max. Allowable Free Fall (ft.) | 6 |
| Max. Arrest Force | 1800 lb, 900 lb (4 kN) |
| Nominal Length (ft.) | 4 |
| Number of Hooks | 2 |
| Special Features | Tear-Webbing Shock Absorber |
| Standards | CSA Z259.11-17 |
| Style | Shock Absorbing, Webbing |
| Weight | 110 lb to 220 |

