

AUTO-RANGING DIGITAL MULTIMETER

Product # 310008 | Model # JDMM-300



- Versatile meters for a wide range of electrical tests
- Features auto shut-off, large LCD display, low battery indicator, overload protection
- TPR shroud protects meter
- Can be used with clamp on adaptor for expanded versatility
- Includes test leads, K-type thermo-coupler and 9V battery
- Automatically sets correct range when test function is selected
- Mechanically prevents incorrect connection of test leads
- Data hold function
- Designed to safety standard EN61010-1; CAT II 600V



TECHNICAL SPECIFICATIONS

AC Current	400u-4000u-40m-400m-4A-20A
AC Voltage	400mV-4V-40V-400V-750V
Application	AC/DC current, AC/DC voltage, resistance, capacitance, frequency, temperature, diode check, duty cycle, continuity check
Capacitance	40nF-400nF-4uF-40uF-100uF
Continuity Check	Threshold 30 ohms, continuity beeper 2.7 kHz
DC Current	400u-4000u-40m-400m-4A-20A
DC Voltage	400mV-4V-40V-400V-1000V
Diode Check	Test current of 0.3 mA, open circuit voltage of 1.5 V
Duty Cycle	0.1 – 99.9%
Frequency	9.999 Hz – 9.999 MHz
Resistance	200-4k-40k-400k-4Mohms-40 Mohms
Temperature	-20°C to 760°C

