



**PEAKWORKS®**



**DUAL TIE-BACK**  
**SRL**

Self- Retracting Lifelines

[www.surewerx.com/usa](http://www.surewerx.com/usa)






Sharp Steel Edges

## Working on the Edge.

If you work in a leading edge environment you have several unique risks to keep in mind when choosing fall protection equipment. Exposure to fall hazards when working near a drop off edge or ledge and increased risk of lifeline failure in a sharp edge condition are different from typical fall protection needs. PeakWorks offers an SRL Leading Edge (LE) series that meets the new ANSI Leading Edge (LE) standard.




Sharp Edge Conditions

## Why Choose a PeakWorks SRL LE Device?


- PeakWorks leading edge self retracting lifelines are certified to the most up to date ANSI Z359.14 standard.
- PeakWorks offers certified leading-edge products that have been designed without the need for external shock absorbers. This means that less distance needs to be added to total fall arrest calculations. PeakWorks offers Class A leading edge SRLs where the fall arrest distance is 24" or less compared to 48" when an external shock absorber is needed.
- All PeakWorks leading edge self-retracting lifelines are clearly marked to ensure that the correct SRL is used for leading edge applications.
- Units are lightweight and can be mounted on a worker's harness for better mobility and range of motion. They can also be mounted below a worker's fall arrest D-Ring on dual configurations.
- PeakWorks leading edge self-retracting lifelines are tested for both overhead and leading-edge applications including perpendicular edge and lateral offset tests.
- These test protocols ensure that if a worker falls over a steel sharp edge, the SRL will successfully arrest the fall.



Sharp Edge Conditions



Global Sharp Edge Symbol  
Radius as sharp as  
.005 in. (.13 mm)



Failure due to sharp edge  
conditions



# Dual Tie-Back SRL

Bracket connector allows for easy installation under the D-ring

Swivel top keeps the life line from tangling and twisting

100% tie off with a dual SRL

Among the smallest and most durable SRLs in the market

Hi-Visibility green Dyneema® webbing allows you to see workers connected at heights

Abrasion-resistant outer jacket tie back legs wrap around the anchor point allowing the tie-back snap hook to tie back on to itself

## We Know That Working Smart Is Working Safe.

At SureWerx we are passionate about the safety and productivity of the professional worker. It is in this spirit that we are proud to announce the availability of a new all in one tie-back self-retracting lifeline. The tie-back is a lightweight design with innovative solutions that eliminate the need for separate anchorage connectors. The new tie-back can wrap around a 5,000 lb anchorage and connect back onto itself. Also included is a 3 foot protective sleeve that guards against abrasions on the lanyard webbing. The dual lanyard provides 100% tie off which means extra protection when changing between anchorage points. We are confident this new SRL will provide both the peace of mind and confidence to take on any job.

- Available in single and dual
- 100% Tie off with the dual SRL
- Overhead and Foot level tie-off approved
- No anchor connectors needed
- Light weight 6 lb. (2.7kg)
- Compact design for comfort and reduced user fatigue
- Impact resistant aluminum housing for maximum durability when compared to nylon or thermoplastic housing
- Internal braking mechanism is built in. No external shock pack required
- Hi-Vis green webbing let's you know workers are connected
- Certified for Leading Edge (LE) to ANSI Z359.14
- Third Party Tested
- Replaces shock absorbing lanyards
- 9 ft. working length increases mobility & flexibility

### Using the correct snap hook on the SRL tie-back makes all the difference.

Peakworks designed the new Tie-Back with a special snap hook that will not accidentally open under gate load. Be sure to use approved Tie-Back gear that is certified to meet ANSI standards 5,000 lb. gate strength







## Dual Tie-Back SRL

### Compact Unit

Among the smallest SRLs in the market. Designed for comfort and reduce fatigue.

Impact-Resistant Aluminum housing provides maximum durability compared to nylon or thermoplastic housing SRLs in the market. Internal automatic locking pawls will stop a fall within inches while keeping average arresting forces to 900 lbs. or less. Unlike competitor SRLs, no external shock pack is required on any of the peakworks SRLs as shock absorbers capability are built in to the internal braking mechanism.

Tie-back snap hook with a 5,000 lb. Gate strength and 0.83" (21 mm) gate opening.

Bracket connector allows for easy installation under the D-ring and provides a snug backpack style fit. No separate carabiner required for harness connectivity on dual SRLs. Provides 360 degree rotation and leaves the harness dorsal D-ring open for rescue or other equipment attachment.

Swivel top keeps the life line from tangling and twisting.

6 ft. retractable lifeline reduces dragging and trip falls.

Hi-Visibility green Dyneema® webbing allows workers to easily inspect webbing for damage.


3 ft. of Abrasion-resistant outer jacket tie back legs wrap around the anchor point allowing the tie-back snap hook to tie back on to itself.

Offers more mobility for workers allowing the tie-back leg to connect where traditional anchorage connectors are not available or feasible.

Impact Indicator provides visual inspection.



Product No. V845528009TB



Use the PeakWorks app for calculating fall clearances

800-323-7402

[surewerx.com/usa](http://surewerx.com/usa)

