

# SHOCK ABSORBING LANYARD - SP - TWIN LEG - SNAP HOOKS - 6' (1.8 M) - 200 - 350 LB CAPACITY

Product # **V8104906** | Model # **SA-64000-6**



SP (Shock Pack) lanyards are comprised of tear webbing which is woven in a manner that allows the webbing to tear when it has a load applied to it. This tearing absorbs a significant amount of downward force under load, reducing injury. This tear webbing is folded and shrink-wrapped into a compact 1 x 2 x 6 (2.5 x 5 x 15 cm) pack that is sewn into the lanyard next to the body connector.

- Certified to CSA Z259.11-05 standards
- Made with a superior grade, heavy-duty 1" (25 mm) polyester webbing for maximum strength with tear webbing shock absorber
- A tearaway absorber limits the arrest force to a maximum of 1800 lbf (8.0 kN) and an average arrest force of less than 1350 lbf (6.0 kN)
- PeakWorks E6 SP lanyards have a capacity range of 200–350 lbs (9 –159 kg)



## TECHNICAL SPECIFICATIONS

Anchor Hook Type	Snap Hook
Body Hook Type	Snap Hook
Deceleration Distance	4.4 ft at 350 lbs
Hooks	3 snap hooks (1 body, 2 anchor)
Leg Type	Twin
Length (ft.)	6
Length (m.)	1.8
Length/Configuration	6' (1.8 m), double leg, 100% tie off
Material	Polyester Webbing
Max. Allowable Free Fall	6 ft
Max. Allowable Free Fall (ft.)	6
Max. Arrest Force	1,300 lb (6 kN), 1800 lb
Nominal Length (ft.)	6
Number of Hooks	3
Special Features	Tear-Webbing Shock Absorber
Standards	CSA Z259.11-17

Style	Webbing, Shock Absorbing
Weight (lb)	5.0 lb
Weight Capacity (lbs.)	200 lb to 350 lb