

# 5 TON KCH SERIES CHAIN HOIST WITH OVERLOAD PROTECTION - HEAVY DUTY



Product # 101356 | Model # KCH-5020L

- Equipped with an automatic overload protection device as standard equipment (up to 5 tons)
- Device is factory preset to prevent serious overload of the hoist
- Actuation is automatic, requiring no input from the operator
- Triple Spur geared for efficient operation
- Grade 100 load chain for greater strength
- Exclusive premium grade, non-asbestos brake discs for longest life
- Load tested to 150% of rated capacity with certificate
- Meets ASME B30.16 standards
- ISO 9001-2000 certified factory
- NOTE: Custom Lifts are available in any length desired. Ask your local JET distributor for details!



## TECHNICAL SPECIFICATIONS

A	7-1/2"
B	11-1/8"
C	2-5/8"
D	2-1/2"
E	51 mm
F	60 mm
Force Req. to Lift Capacity	83 lb
G	78 mm
H	23-5/8"
Head Room	23-5/8"
Length of Hand Chain Pulled to Lift Load 1'	198"
Load Chain Diameter	9.0 mm
Number of Falls	2
Rated Lifting Capacity	5 T, 11,000 lb
Shipping Weight	122.2 lb (55.6 kg)
Standard Lift	20'

