

1" DRIVE IMPACT WRENCH (2" ANVIL)

Product # 400455 | Model # AW25AD2



- Produces 1,900 ft/lbs of hard hitting torque
- Rocking dog hammer mechanism for power and durability
- D-handle design complete with side handle for maximum operator control
- Forward and reverse valve is equipped with position throttle settings
- Exhaust outlet directs air away from operator for maximum safety and comfort
- Three piece construction allows quick, easy maintenance
- Air inlet screen for extended motor life
- For maximum performance we recommend 90 - 120 PSI air pressure
- Ideal for truck and tractor tire work, agricultural and general shop applications



TECHNICAL SPECIFICATIONS

Air Inlet (NPT)	1/2"
Anvil	2"
Average Air Consumption	10 cfm
Free Speed	4,000 RPM
Max. Torque - Forward	1,900 ft-lb
Max. Torque - Reverse	1,900 ft-lb
Min. Hose Size	3/4"
Overall Length	15.26"
Product Weight	25.73 lb (11.60 kg)
Sound Pressure	103.4 dBA
Square Drive	1"
Standard Bolt Capacity	1.77"

Vibration	< 0.4 m/s ²
Working Torque - Forward	1,500 – 1,650 PSI
Working Torque - Reverse	1,500 – 1,650 PSI