

CABLE SRL WITH RECOVERY – 60'

Product # V845643060 | Model # SRL-73303-60



PeakWorks offers a new series of self-retracting lifelines that are third-party certified to the newest CSA Z259.2.2 for overhead use. The lightweight, durable, aluminum housing unit is approved for use in vertical applications. The attachment points include a convenient carrying handle on housing and double-action locking snap hooks with fall indicator to connect to the worker's fall arrest D-ring.

- The anchor point incorporates a heavy-duty, durable, and convenient swivel eye
- SRLs with webbing feature a sewn-in indicator on the lifeline itself for maximum safety
- Rescue units come with release pins and a two-way winding handle to engage the rescue/recovery mode
- 310 lb (136 kg) capacity for 1 worker (combined weight of person, tools, clothing, etc.)
- Lightweight units can be mounted on a worker's harness for better mobility and range of motion
- Features a sewn-in indicator on the lifeline itself for maximum safety



TECHNICAL SPECIFICATIONS

Anchor Hook Material	Steel
Anchor Hook Type	Carabiner
Average Arrest Force	8kN (1800 lbf), 8kN (1350 lbf)
Body Hook Type	Snap Hook
Capacity (kg.)	141
Capacity (lb.)	310
Class Type	B
Color	Black
Gate Opening (in.)	3/4
Gate Opening (mm.)	19
Housing Material	Aluminum
Leading Edge	No
Leg Type	Single
Length (ft.)	60
Length (m.)	18.288
Lifeline Material	Galvanized Steel
Minimum Fall	N/A

Clearance - Leading Edge application (ft.)	
Minimum Fall Clearance - Leading Edge applications (m)	N/A
Nominal Length (ft.)	60
Rescue and Recover - SRL-R	No
Standards	CSA Z259.2.2-2017 ANSI Z359.14-2014, Class B
Webbing/Cable Thickness (in.)	.21
Webbing/Cable Thickness (mm.)	5.5