

SHOCK ABSORBING LANYARD - SP - TWIN LEG - SNAP & FORM HOOKS - 4' (1.2 M) - 110 – 220 LB CAPACITY

Product # V8104824 | Model # SA-54022-4



SP (Shock Pack) lanyards are comprised of tear webbing which is woven in a manner that allows the webbing to tear when it has a load applied to it. This tearing absorbs a significant amount of downward force under load, reducing injury. This tear webbing is folded and shrink-wrapped into a compact 1 x 2 x 6 (2.5 x 5 x 15 cm) pack that is sewn into the lanyard next to the body connector.

- Certified to CSA Z259.11-05 standards
- Made with a superior grade, heavy-duty 1" (25 mm) polyester webbing for maximum strength with tear webbing shock absorber
- A tearaway absorber limits the arrest force to a maximum of 900 lbf (4.0 kN) and an average arrest force of less than 675 lbf (3.0 kN)
- PeakWorks E4 SP lanyards have a capacity range of 110–220 lbs (50–100 kg)



TECHNICAL SPECIFICATIONS

| | |
|--------------------------------|---|
| Anchor Hook Type | Form Hook |
| Body Hook Type | Snap Hook |
| Deceleration Distance | 4 ft at 220 lbs |
| Hooks | 1 snap hook (body), 2 form hooks (anchor) |
| Leg Type | Twin |
| Length (ft.) | 4 |
| Length (m.) | 1.2 |
| Length/Configuration | 4' (1.2 m), double leg, 100% tie off |
| Material | Polyester Webbing |
| Max. Allowable Free Fall | 6 ft |
| Max. Allowable Free Fall (ft.) | 6 |
| Max. Arrest Force | 900 lb (4 kN), 1,800 lb (8 kN), 1800 lb |
| Nominal Length (ft.) | 4 |
| Number of Hooks | 3 |
| Special Features | Tear-Webbing Shock Absorber |

| | |
|---------------------------|--------------------------------|
| Standards | CSA Z259.11-17 |
| Style | Webbing, Shock Absorbing |
| Weight (lb) | 6.0 lb |
| Weight Capacity (lbs.) | 110 lb to 220 lb |