

Safety Data Sheet

Diamond Products

Issue Date: 03/01/2019

1. Product and Company Identification

GHS Product Identifier: JET-KUT

Product Numbers: 568602, 568609, 568615, 568632, 568643, 568652, 568663, 567010, 567015, 567025, 567040, 568603, 568611, 568617, 568633, 568645, 568655, 568666, 567010, 567115, 567125, 56714, 568601, 568614, 568631, 568661, 567405, 567440, 568729, 568739, 569801, 569811, 568812, 568814, 568824, 568826, 568836, 568815, 568825, 568827, 569806, 569816, 567202, 567222, 567212, 567232

Manufacturer/Supplier

Supplier: JET EQUIPMENT & TOOLS

Address: 49 Schooner Street, Coquitlam, BC Canada

Telephone: 604-523-8665

Fax: 604-523-7691

2. Hazards Identification

Precautionary Statements

Avoid inhalation of dusts as well as prolonged and repeated contact with skin. Most diamond tools are used along with water to keep blades cool and to decrease airborne contaminants. For dry sawing and grinding, maintain adequate ventilation or use local exhaust.

Description of Hazards

Dust created by grinding and/or sawing can cause irritation to eyes, nose, throat and skin.

Long term overexposure to dusts can lead to respiratory impairment.

Grinding or sawing may produce an elevated noise which can affect hearing.

Particles of various size ejected during grinding or sawing may pose impact hazards to eyes and skin.

3. Composition/Information on Ingredients

Components	CAS#	%
Fe	7439-89-6	40-50%
Cu	7440-50-8	40-50%
Tungsten Carbide (wc)	12070-12-1	2-10%
Cobalt (Co)	7440-78-7	5-10%

4. First Aid Measures

Inhalation: If exposed to dust from grinding: Remove victim to fresh air. Give artificial respiration if needed. If breathing is difficult, oxygen should be administered by qualified personnel. Get medical attention if breathing is difficult or irritation persists.

Skin contact: Wash dust from skin with soap and water. Launder contaminated clothing before reuse.

Eye contact: Do not rub. Flush eyes thoroughly with plenty of water, holding open eyelids. Get medical attention if irritation persists. Obtain immediate medical attention for foreign body in the eye.

Ingestion: If grinding dust is swallowed, seek medical attention.

Most important symptoms/effects, acute and delayed: Eye and skin contact with grinding dust may cause mechanical irritation. Inhalation of dust may cause dizziness, headache, and other central nervous system effects. Prolonged inhalation of dust or fumes from this product may cause perforation of the nasal septum and lung damage. Exposure to dust generated from processing the base material or coatings may present additional health hazards. This product contains titanium dioxide, which are suspected of causing cancer based on animal studies. Risk of cancer depends on duration and level of exposure.

Indication of immediate medical attention and special treatment, if necessary: Immediate medical attention is generally not required.

5. Fire Fighting Measures

Suitable (and unsuitable) extinguishing media: Use any media that is appropriate for the surrounding materials.

Specific hazards arising from the chemical: This product is not combustible; however, consideration must be given to the potential fire or explosion hazards from the base material being processed. Many materials create flammable or explosive dusts or turnings when machined or ground.

Special protective equipment and precautions for firefighters: Firefighters should wear full emergency equipment and NIOSH approved positive pressure self-contained breathing apparatus.

6. Accidental Release Measures

Personal precautions, protective equipment, and emergency procedures: N/A

Methods and materials for containment and cleaning up: N/A

7. Handling and Storage

Precautions for safe handling: Do not breathe dust. Use with adequate ventilation. Avoid eye and skin contact with grinding dust. Wear suitable gloves, eye protection and appropriate protective clothing according to the operation. Wash thoroughly after handling. Consider potential exposure to components of the base materials or coatings being ground. Refer to OSHA's substance specific standards for additional work practice requirements where applicable.

Conditions for safe storage, including any incompatibilities: Store in a dry location.

8. Exposure Controls/Personal Protection

Appropriate engineering controls: Use local exhaust or general ventilation as required to minimize exposure to dust and maintain the concentration of contaminants below the TLVs.

Individual protection measures, such as personal protective equipment:

Respiratory protection: Use NIOSH approved respirator if exposure limits are exceeded or where dust exposures are excessive. Consider the potential for exposure to components of the coatings or base material being ground in selecting proper respiratory protection. Refer to OSHA's specific standards for lead, cadmium, etc. where appropriate. Selection of respiratory protection depends on the contaminant type, form and concentration. Select and use respirators in accordance with OSHA 1910.134 and good industrial hygiene practice.

Skin protection: Cloth or leather gloves recommended.

Eye protection: Safety goggles or safety glasses with side shields are recommended where splashing is possible.

Other: Protective clothing as needed to prevent contamination of personal clothing. Hearing protection may be required.

9. Physical and Chemical Properties

Boiling point: Not applicable

Vapor Pressure: (mm Hg) Not applicable

Solubility in Water: Insoluble

Vapor Density: (air=1) Not applicable

Specific Gravity: Not applicable

Evaporation Rate: Not applicable

Melting Point: Not applicable

Flash Point: Non-combustible

Appearance and Odor: Gray: metal, no odor.

10. Chemical Stability and Reactivity Information

Reactivity: Not reactive.

Chemical stability: Stable

Possibility of hazardous reactions: Will not occur.

Conditions to avoid: None known.

Incompatible materials: Strong acids and bases

Hazardous decomposition products: Dust from grinding could contain ingredients listed in

Section 3 and other, potentially more hazardous components of the base material being ground or coatings applied to the base material.

11. Toxicological Information

Likely routes of exposure:

Inhalation: May cause respiratory tract irritation with coughing, mucous production and shortness of breath. High concentration is irritating to the respiratory tract and may cause dizziness, headache and anesthetic effects.

Ingestion: None expected under normal use conditions. Swallowing large pieces may cause obstruction of the gastrointestinal tract.

Skin contact: None expected under normal use conditions. Rubbing product across the skin may cause mechanical irritation or abrasions.

Eye contact: Dust particles may cause abrasive injury to the eyes.

Chronic effects from short- and long-term exposure: Long-term overexposure to respirable dust may cause lung damage (fibrosis) with symptoms of coughing, shortness of breath and diminished breathing capacity. Risk of cancer depends on the level and duration of exposure. Chronic effects may be aggravated by smoking. Prolonged exposure to elevated noise levels during operations may affect hearing. A greater hazard, in most cases, is the exposure to the dust/fumes from the material or paint/coatings being ground. Most of the dust generated during grinding is from the base material being ground and the potential hazard from this exposure must be evaluated.

12. Ecological information

Products have no ecological effects when properly used and stored. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

No data available.

13. Disposal Considerations

Dispose in accordance with all applicable local, state/provincial and federal regulations. Local regulations may be more stringent than regional and national requirements. It is the responsibility of the waste generator to determine the toxicity and physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations.

14. Transport Information

No specific regulations for transportation are required. Make sure to protect products from damage during transportation.