

2 STAGE 30/15 TON AIR HYDRAULIC TRUCK JACK - SUPER HEAVY DUTY

Product # 030474 | Model # 730SHD

STRONGARM®



- The extra light weight and portability makes this the ideal service jack for service vehicles
- 2 stages and lifting capacities of 30 and 15 ton make this a very versatile jack
- The extra long removable handle and rugged rear wheels make for easy positioning of this jack in hard to reach places
- An integral Descent Metering Valve maintains a controlled and safe lowering of the load
- The piston head seal design is borrowed from industrial technology providing a superior low and high pressure seal, giving this jack a much better hold under severe load conditions
- Double polished chromed pistons allow for much tighter tolerances which reduce oil bypassing and reduced ram scoring
- Air assisted lowering speeds up ram retraction
- Built-in overload safety valve prevents damage to unit due to excessive load
- Comes with 2 extensions (75mm & 45mm) and saddle adapter
- Units are tested to -25°C and +45°C as well as off centre loading to ensure a long life under even the harshest conditions



TECHNICAL SPECIFICATIONS

Capacity	30 T (1st Stage) / 15 T (2nd Stage)
High Height	15 Ton - 292 mm (11.5") Lift - 142 mm (5.59"), 30 Ton - 224 mm (8.82") Lift - 74 mm (2.91")
Low Height	150 mm (5.92")
Product Weight	66 lb (30 kg)
Shipping Weight	77 lb (35 kg)
Working Air Pressure	30 Ton - 0.8 – 1.0 Mpa (116 – 145 PSI)