

3 TON KCH SERIES CHAIN HOIST WITH OVERLOAD PROTECTION - HEAVY DUTY

Product # 101346 | Model # KCH-3020L



- Equipped with an automatic overload protection device as standard equipment (up to 5 tons)
- Device is factory preset to prevent serious overload of the hoist
- Actuation is automatic, requiring no input from the operator
- Triple Spur geared for efficient operation
- Grade 100 load chain for greater strength
- Exclusive premium grade, non-asbestos brake discs for longest life
- Load tested to 150% of rated capacity with certificate
- Meets ASME B30.16 standards
- ISO 9001-2000 certified factory
- NOTE: Custom Lifts are available in any length desired. Ask your local JET distributor for details!



TECHNICAL SPECIFICATIONS

A	6-5/8"
B	9-1/4"
C	4-1/8"
D	2-1/16"
E	43.5 mm
F	52 mm
Force Req. to Lift Capacity	79 lb
G	62.5 mm
H	20"
Head Room	20"
Length of Hand Chain Pulled to Lift Load 1'	114'
Load Chain Diameter	7.1 mm
Number of Falls	2
Rated Lifting Capacity	3 T, 6,600 lb
Shipping Weight	73.6 lb (33.5 kg)
Standard Lift	20'

