

3 STAGE 60/40/20 TON AIR HYDRAULIC TRUCK JACK - SUPER HEAVY DUTY

Product # 030476 | Model # 760SHD

STRONGARM®



- This Super Heavy Duty, 3 Stage 60/40/20 Ton Air Hydraulic Jack covers a wide variety of demands from the heavy duty trucking, agricultural, fleet, construction and military sectors
- The piston head seal design is borrowed from industrial technology providing a superior low and high pressure seal, giving this jack a much better hold under severe load conditions
- The extra long 138cm (54") handle can be locked in 3 positions for easy positioning of this jack in hard to reach places
- An integral Descent Metering Valve maintains a controlled and safe lowering of the load
- Single piece base construction provides superior strength for increased load stability
- Double polished chromed pistons allow for much tighter tolerances which reduce oil bypassing and reduced ram scoring
- Air assisted lowering speeds up ram retraction
- Built-in overload safety valve prevents damage to unit due to excessive load
- Comes with 2 extensions (75mm + 45 mm) and saddle adaptor
- Units are tested to -25°C and + 45°C as well as off centre loading to ensure a long life under even the harshest conditions



TECHNICAL SPECIFICATIONS

Capacity	60 T (1st Stage) / 40 T (2nd Stage) / 20 T (3rd Stage)
High Height	60 Ton - 252 mm (9.92") Lift - 77 mm (3.03"), 20 Ton - 404 mm (15.91") Lift - 229 mm (9.02"), 40 Ton - 322 mm (12.68") Lift - 147 mm (5.79")
Low Height	175 mm (6.89")
Product Weight	161 lb (72 kg)
Shipping Weight	165 lb (75 kg)
Working Air Pressure	60 Ton - 0.8 – 1.2 Mpa (116 – 174 PSI)