

# 2 TON KCH SERIES CHAIN HOIST WITH OVERLOAD PROTECTION - HEAVY DUTY

Product # 101332 | Model # KCH-2010L



- Equipped with an automatic overload protection device as standard equipment (up to 5 tons)
- Device is factory preset to prevent serious overload of the hoist
- Actuation is automatic, requiring no input from the operator
- Triple Spur geared for efficient operation
- Grade 100 load chain for greater strength
- Exclusive premium grade, non-asbestos brake discs for longest life
- Load tested to 150% of rated capacity with certificate
- Meets ASME B30.16 standards
- ISO 9001-2000 certified factory
- NOTE: Custom Lifts are available in any length desired. Ask your local JET distributor for details!



## TECHNICAL SPECIFICATIONS

A	7-1/4"
B	8"
C	2-1/2"
D	1-3/8"
E	37 mm
F	46 mm
Force Req. to Lift Capacity	79 lb
G	52 mm
H	14-3/4"
Head Room	14-3/4"
Length of Hand Chain Pulled to Lift Load 1'	70'
Load Chain Diameter	8.0 mm
Number of Falls	1
Rated Lifting Capacity	4,400 lb, 2 T
Shipping Weight	45.2 lb (20.6 kg)
Standard Lift	10'