

2 STAGE 50/25 TON AIR HYDRAULIC TRUCK JACK - SUPER HEAVY DUTY

Product # 030475 | Model # 750SHD

STRONGARM®



- Super Heavy Duty, 2 Stage 50 Ton and 25 Ton built tough for the rigors of the heavy duty trucking, agricultural and fleet business
- The piston head seal design is borrowed from industrial technology providing a superior low and high pressure seal, giving this jack a much better hold under severe load conditions
- The extra long 138cm (54") handle can be locked in 3 positions for easy positioning of this jack in hard to reach places
- An integral Descent Metering Valve maintains a controlled and safe lowering of the load
- Single piece base construction provides superior strength for increased load stability
- Double polished chromed pistons allow for much tighter tolerances which reduce oil bypassing and reduced ram scoring
- Air assisted lowering speeds up ram retraction
- Built-in overload safety valve prevents damage to unit due to excessive load
- Comes with 2 extensions (75mm & 45mm) and saddle adaptor
- Units are tested to -25°C and +45°C as well as off centre loading to ensure a long life under even the harshest conditions



TECHNICAL SPECIFICATIONS

| | |
|----------------------|--|
| Capacity | 50 T (1st Stage) / 25 T (2nd Stage) |
| High Height | 50 Ton - 332 mm (13.07") Lift - 117 mm (4.61"), 25 Ton - 446 mm (17.56") Lift - 231 mm (9.09") |
| Low Height | 215 mm (8.46") |
| Product Weight | 161 lb (72 kg) |
| Shipping Weight | 165 lb (75 kg) |
| Working Air Pressure | 50 Ton - 0.8 – 1.2 Mpa (116 – 174 PSI) |