

5 TON KCH SERIES CHAIN HOIST WITH OVERLOAD PROTECTION - HEAVY DUTY

Product # 101352 | Model # KCH-5010L



- Equipped with an automatic overload protection device as standard equipment (up to 5 tons)
- Device is factory preset to prevent serious overload of the hoist
- Actuation is automatic, requiring no input from the operator
- Triple Spur geared for efficient operation
- Grade 100 load chain for greater strength
- Exclusive premium grade, non-asbestos brake discs for longest life
- Load tested to 150% of rated capacity with certificate
- Meets ASME B30.16 standards
- ISO 9001-2000 certified factory
- NOTE: Custom Lifts are available in any length desired. Ask your local JET distributor for details!



TECHNICAL SPECIFICATIONS

A	7-1/2"
B	11-1/8"
C	2-5/8"
D	2-1/2"
E	51 mm
F	60 mm
Force Req. to Lift Capacity	83 lb
G	78 mm
H	23-5/8"
Head Room	23-5/8"
Length of Hand Chain Pulled to Lift Load 1'	198'
Load Chain Diameter	9.0 mm
Number of Falls	2
Rated Lifting Capacity	5 T, 11,000 lb
Shipping Weight	93.6 lb (42.6 kg)
Standard Lift	10'